



A-GAS R410A

A-Gas (Singapore) PTE LTD

Chemwatch: 6100-24

Version No: 5.1.1.1

Material Safety Data Sheet according to NOHSC and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 09/09/2013

Print Date: 07/03/2014

Initial Date: Not Available

S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	A-GAS R410A
Chemical Name	A-Gas R410A
Synonyms	Not Available
Proper shipping name	LIQUEFIED GAS, N.O.S. (contains difluoromethane and pentafluoroethane)
Chemical formula	Not Available
Other means of identification	Not Available
CAS number	133023-17-3

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	A-Gas (Singapore) PTE LTD
Address	360 Orchard Road, #10-05, Int'l Building 238869 Singapore
Telephone	65 6836 0065
Fax	65 6836 6521
Website	www.agas.com
Email	Not Available

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	65 6836 0065
Other emergency telephone numbers	65 6836 0065

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

DANGEROUS GOODS. NON-HAZARDOUS SUBSTANCE. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		0 = Minimum
Toxicity	2		1 = Low
Body Contact	2		2 = Moderate
Reactivity	1		3 = High
Chronic	2		4 = Extreme

Poisons Schedule	
Risk Phrases [1]	R44 Risk of explosion if heated under confinement. R04 Forms very sensitive explosive metallic compounds.
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
GHS Classification	Not Applicable

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements

SIGNAL WORD **NOT APPLICABLE**

Hazard statement(s)

AUH044 Risk of explosion if heated under confinement

Precautionary statement(s): Prevention

Not Applicable

Precautionary statement(s): Response

Not Applicable

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

Not Applicable

Label elements

Relevant risk statements are found in section 2

Indication(s) of danger Not Applicable

SAFETY ADVICE

- | | |
|------------|--|
| S03 | Keep in a cool place. |
| S15 | Keep away from heat. |
| S56 | Dispose of this material and its container at hazardous or special waste collection point. |

Other hazards

- May produce discomfort of the respiratory system and skin*.
- Inhalation may produce health damage*.
- Cumulative effects may result following exposure*.
- Vapours potentially cause drowsiness and dizziness*.
- Repeated exposure potentially causes skin dryness and cracking*.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

CAS No	%[weight]	Name
75-10-5	50	difluoromethane
354-33-6	50	pentafluoroethane

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<ul style="list-style-type: none"> ▶ If product comes in contact with eyes remove the patient from gas source or contaminated area. ▶ Take the patient to the nearest eye wash, shower or other source of clean water. ▶ Open the eyelid(s) wide to allow the material to evaporate. ▶ Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners. ▶ The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage. ▶ Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) ▶ Transport to hospital or doctor. ▶ Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. ▶ If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage. ▶ Ensure verbal communication and physical contact with the patient. <p>DO NOT allow the patient to rub the eyes DO NOT allow the patient to tightly shut the eyes DO NOT introduce oil or ointment into the eye(s) without medical advice DO NOT use hot or tepid water.</p>
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.

Inhalation	<ul style="list-style-type: none"> ▶ Following exposure to gas, remove the patient from the gas source or contaminated area. ▶ NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. ▶ Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If the patient is not breathing spontaneously, administer rescue breathing. ▶ If the patient does not have a pulse, administer CPR. ▶ If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. ▶ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. ▶ Keep the patient warm, comfortable and at rest while awaiting medical care. ▶ MONITOR THE BREATHING AND PULSE, CONTINUOUSLY. ▶ Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	<ul style="list-style-type: none"> ▶ Not considered a normal route of entry. ▶ For advice, contact a Poisons Information Centre or a doctor. ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol.

Indication of any immediate medical attention and special treatment needed

	<p>for intoxication due to Freons/ Halons;</p> <p>A: Emergency and Supportive Measures</p> <ul style="list-style-type: none"> ▶ Maintain an open airway and assist ventilation if necessary ▶ Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV. ▶ Monitor the ECG for 4-6 hours <p>B: Specific drugs and antidotes:</p> <ul style="list-style-type: none"> ▶ There is no specific antidote <p>C: Decontamination</p> <ul style="list-style-type: none"> ▶ Inhalation; remove victim from exposure, and give supplemental oxygen if available. ▶ Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes) <p>D: Enhanced elimination:</p> <ul style="list-style-type: none"> ▶ There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal. <p><i>POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition</i></p> <ul style="list-style-type: none"> ▶ Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability. ▶ No specific antidote. ▶ Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician. ▶ If lavage is performed, suggest endotracheal and/or esophageal control. ▶ Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. ▶ Treatment based on judgment of the physician in response to reactions of the patient <p>for gas exposures:</p> <p>-----</p> <p>BASIC TREATMENT</p> <p>-----</p> <ul style="list-style-type: none"> ▶ Establish a patent airway with suction where necessary. ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary. ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min. ▶ Monitor and treat, where necessary, for pulmonary oedema . ▶ Monitor and treat, where necessary, for shock. ▶ Anticipate seizures. <p>-----</p> <p>ADVANCED TREATMENT</p> <p>-----</p> <ul style="list-style-type: none"> ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred. ▶ Positive-pressure ventilation using a bag-valve mask might be of use. ▶ Monitor and treat, where necessary, for arrhythmias. ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications. ▶ Drug therapy should be considered for pulmonary oedema. ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications. ▶ Treat seizures with diazepam. ▶ Proparacaine hydrochloride should be used to assist eye irrigation. <p><i>BRONSTEIN, A.C. and CURRANCE, P.L.</i> <i>EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994</i></p>
--	--

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<p>SMALL FIRE: Use extinguishing agent suitable for type of surrounding fire.</p> <p>LARGE FIRE: Cool cylinder.</p>
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<p>-----</p> <p>GENERAL</p> <p>-----</p>
----------------------	--

	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Containers may explode when heated - Ruptured cylinders may rocket ▶ Fire exposed containers may vent contents through pressure relief devices. ▶ High concentrations of gas may cause asphyxiation without warning. ▶ May decompose explosively when heated or involved in fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. ▶ DO NOT enter confined spaces were gas may have accumulated.
Major Spills	<ul style="list-style-type: none"> ▶ Clear area of all unprotected personnel and move upwind. ▶ Alert Emergency Authority and advise them of the location and nature of hazard. ▶ Wear breathing apparatus and protective gloves. ▶ Prevent by any means available, spillage from entering drains and water-courses.
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Vented gas is more dense than air and may collect in pits, basements.
Other information	<ul style="list-style-type: none"> ▶ Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. ▶ Such compounds should be sited and built in accordance with statutory requirements. ▶ The storage compound should be kept clear and access restricted to authorised personnel only. ▶ Cylinders stored in the open should be protected against rust and extremes of weather.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ DO NOT use aluminium or galvanised containers <p>[Cylinder: Steel Packaging]Ensure the use of equipment rated for cylinder pressure.[Ensure the use of compatible materials of construction.[Valve protection cap to be in place until cylinder is secured, connected.[Cylinder must be properly secured either in use or in storage.[Cylinder valve must be closed when not in use or when empty.[Segregate full from empty cylinders][WARNING: Suckback into cylinder may result in rupture. Use back-flow preventive device in piping.</p>
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents ▶ Avoid magnesium, aluminium and their alloys, brass and steel. <p>Haloalkanes: ▶ are highly reactive:some of the more lightly substituted lower members are highly flammable; the more highly substituted may be used as fire suppressants, not always with the anticipated results.</p>

PACKAGE MATERIAL INCOMPATIBILITIES

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA


Not Available

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
difluoromethane	1000(ppm)	3000(ppm)	200000(ppm)	350000(ppm)

Ingredient	Original IDLH	Revised IDLH
A-GAS R410A	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below

Hand protection	▶ When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change) ▶ Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated. ▶ Protective overalls, closely fitted at neck and wrist. ▶ Eye-wash unit.
Thermal hazards	

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the A-GAS R410A Not Available

Material	CPI
----------	-----

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P3	-	AX-PAPR-AUS / Class 1 P3
up to 50 x ES	-	AX-AUS / Class 1 P3	-
up to 100 x ES	-	AX-2 P3	AX-PAPR-2 P3 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Appearance	Colourless liquefied gas with a slight ethereal odour; does not mix with water.		
Physical state	Liquefied Gas	Relative density (Water = 1)	1.11 @ 15 deg.C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Neutral	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-103 (R125); -136 (R32) (freezing point)	Viscosity (cSt)	0.150 @ 25 deg.C
Initial boiling point and boiling range (°C)	-52.7	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	100
Vapour pressure (kPa)	1246 @ 15 deg.C	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Applicable
Vapour density (Air = 1)	2.3	VOC g/L	

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. ▶ Extremely high temperatures.

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Symptoms of asphyxia (suffocation) may include headache, dizziness, shortness of breath, muscular weakness, drowsiness and ringing in the ears. If the asphyxia is allowed to progress, there may be nausea and vomiting, further physical weakness and unconsciousness and, finally, convulsions, coma and death.
Ingestion	Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	In common with other halogenated aliphatics, fluorocarbons may cause dermal problems due to a tendency to remove natural oils from the skin causing irritation and the development of dry, sensitive skin. They do not appear to be appreciably absorbed.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Principal route of occupational exposure to the gas is by inhalation. It is generally accepted that the fluorocarbons are less toxic than the corresponding halogenated aliphatic based on chlorine. Repeated inhalation exposure to the fluorocarbon FC-11 does not produce pathologic lesions of the liver and other visceral organs in experimental animals. There has been conjecture in non-scientific publications that fluorocarbons may cause leukemia, cancer, sterility and birth defects; these have not been verified by current research.

A-GAS R410A	TOXICITY	IRRITATION
	Not Available	Not Available
difluoromethane	TOXICITY	IRRITATION
	Inhalation (rat) LC50: >760000 ppm/4h *	(DuPont)
	Not Available	Not Available
pentafluoroethane	TOXICITY	IRRITATION
	Inhalation (rat) LC50: >709000 ppm/4h *	Nil reported * [
	Inhalation (Rat) LC50: 800000 ppm/4h*	
	Not Available	Not Available

* Value obtained from manufacturer's msds

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

A-GAS R410A	Acute toxicity - Inhalation, LC 0, 4 h, rat, > 52 % v/v air (R125/R32) Irritation - No irritation signs noted during toxicity testing. (R125/R32) Chronic toxicity - Inhalation, after a single exposure, dog, >= 10% v/v air, cardiac sensitization following adrenergic stimulation (Data relative to R125) - Inhalation, after repeated exposure, rat, Target organ: central nervous system, >= 5% v/v air (R32) - No mutagenic, teratogenic effects (R125/R32) - Foetotoxic effect (R32)
PENTAFLUOROETHANE	Cardiac sensitisation threshold limit >245400 mg/m3 Anaesthetic effects threshold limit 490800 mg/m3 * DuPont SDS

Acute Toxicity	☉	Carcinogenicity	☉
Skin Irritation/Corrosion	☉	Reproductivity	☉
Serious Eye Damage/Irritation	☉	STOT - Single Exposure	☉
Respiratory or Skin sensitisation	☉	STOT - Repeated Exposure	☉
Mutagenicity	☉	Aspiration Hazard	☉

CMR STATUS

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

In addition to carbon dioxide (CO₂), methane (CH₄) and nitrous oxide (N₂O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and exhibiting very high specific radiative forcing (radiative forcing is the change in the balance between radiation coming into the atmosphere and radiation out; a positive radiative forcing tends on average to warm the surface of the earth). These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF₆).

The greenhouse potential of these substances, expressed as multiples of that of CO₂, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF₆. Once emitted into the atmosphere, these substances have an impact on the environment for decades, centuries, or in certain instances, for thousands of years.

[Mobility]- Air, Henry's law constant (H) ca. 150kPa.m³/mol|Result: considerable volatility|Conditions: 20 °C / calculated value|(Data relative to R125)- Air, Henry's law constant (H) ca. 19.7kPa.m³/mol|Result: considerable volatility|Conditions: 25 °C / calculated value|(R32)- Soil/sediments, adsorption, log KOC from 1.05 - 1.7|Conditions: calculated value|(R125/R32)|Persistence and degradability|Abiotic degradation|- Air, indirect photo-oxidation, t 1/2 = 28.2 year(s)|Conditions: sensitizer: OH radicals|Degradation's products: carbon dioxide / fluorhydric acid / trifluoroacetic acid|(Data relative to R125)- Air, indirect photo-oxidation, t 1/2 = 4.16 year(s)|Conditions: sensitizer: OH radicals|Degradation's products: carbon dioxide / fluorhydric acid|(R32)- Air, photolysis, ODP = 0|Result: no effect on stratospheric ozone|Reference value for CFC 11: ODP = 1. (R125/R32)- Air, greenhouse effect, GWP < 0.5>|Reference value for CFC 11: GWP = 1. (R125/R32)|Biotic degradation|- Aerobic, test ready biodegradability/closed bottle, degradation from 4 - 5 %, 28 day(s)|Result: non-readily biodegradable|(R125/R32)|Bioaccumulative potential|- Bioconcentration: log Po/w from 0.21 - 1.48|Result: non-bioaccumulable|Conditions: measured value|(R125/R32)

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

Mobility in soil

Ingredient	Mobility
Not Available	Not Available


SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Evaporate residue at an approved site. ▶ Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase. ▶ Ensure damaged or non-returnable cylinders are gas-free before disposal.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2TE

Land transport (ADG)

UN number	3163
Packing group	Not Available
UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains difluoromethane and pentafluoroethane)
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 2.2 Subrisk :
Special precautions for user	Special provisions : 274 limited quantity : 120 ml

Air transport (ICAO-IATA / DGR)

UN number	3163
Packing group	Not Available
UN proper shipping name	Liquefied gas, n.o.s. * (contains difluoromethane and pentafluoroethane)
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 2.2 ICAO / IATA Subrisk : ERG Code : 2L
Special precautions for user	Special provisions : Cargo Only Packing Instructions : 200 Cargo Only Maximum Qty / Pack : 150 kg

Passenger and Cargo Packing Instructions	200
Passenger and Cargo Maximum Qty / Pack	75 kg
Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
Passenger and Cargo Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	3163
Packing group	Not Available
UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains difluoromethane and pentafluoroethane)
Environmental hazard	No relevant data
Transport hazard class(es)	IMDG Class : 2.2 IMDG Subrisk :
Special precautions for user	EMS Number : F-C,S-V Special provisions : 274 Limited Quantities : 120 ml

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture**

difluoromethane(75-10-5) is found on the following regulatory lists	"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 15 Ozone depleting substances - Part 9 HFCs", "Sigma-Aldrich Transport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (English)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - non-pesticide anthropogenic organics)", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List"
pentafluoroethane(354-33-6) is found on the following regulatory lists	"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 15 Ozone depleting substances - Part 9 HFCs", "Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (English)", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - non-pesticide anthropogenic organics)"

SECTION 16 OTHER INFORMATION**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.